

REACH-IN FREEZER (0°F)

Model: 1FSEN

Natural Refrigerant R-290 Model

1-Section Slim Line Reach-In Freezer

- 1FSEN** - Stainless steel front, aluminum end panels and interior
- 1FSENSA** - Stainless steel exterior, aluminum interior
- 1FSENSS** - Stainless steel exterior and interior



Options and Accessories

(upcharge and lead times may apply)

| | |
|---|--|
| Stainless steel case back | Shallow depth (consult factory) |
| Additional epoxy coated steel shelves | Hinged glass doors (consult factory) |
| Chrome or stainless steel shelves | Half doors |
| Adjustable legs | Correctional Facility Options |
| Custom laminates | <ul style="list-style-type: none"> • One way security screws |
| Special electrical requirements (consult factory) | <ul style="list-style-type: none"> • Locking hasp (lock not included) • Stainless steel mesh cover • Coverless hinges |

Consult factory for other model configurations, options and accessories.

Continental[®]
Refrigerator



Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

Standard Model Features

REFRIGERATION SYSTEM

Self contained, performance rated refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant¹

Automatic, electric condensate evaporator

Expansion valve system

Standard operating temperature is 0 to -5°F and can be adjusted to operate as low as -10°F in a 90°F ambient.

CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation

Smooth, polished chrome workflow door handle

Cam action, lift off hinges

Self-closing door

Magnetic snap in Santoprene[®] door gasket

Cylinder lock in door

Heavy duty, epoxy coated steel shelves

Heavy duty pilaster strips

5" casters

MODEL FEATURES

LED interior lighting

Electronic control, automatic electric defrost

Will accommodate 12 x 20 pans

Rehinging of doors (in the field)

¹ R-290 refrigerant meets all federal and state regulatory requirements.

APPROVAL:

Model Specifications

DIMENSIONAL DATA

| | |
|--|------------------|
| Net Capacity (cubic feet) | 15 (425 cu l) |
| Width, Overall (inches) | 17 3/4 (451 mm) |
| Depth, Overall (inches) (including handle) | 35 3/8 (899 mm) |
| Depth (inches) (less door) | 32 (813 mm) |
| Depth (inches) (door open 90°) | 49 1/2 (1257 mm) |
| Clear Door Width (inches) | 13 1/8 (333 mm) |
| Clear Door Height (inches) | 60 5/8 (1540 mm) |
| Height, Overall (inches) (including 5" casters) | 82 1/4 (2089 mm) |
| Number of Doors | 1 |
| Number of Shelves | 5 |
| Shelf Area (square feet) | 9.3 (0.9 sq m) |

REFRIGERANT DATA

| | |
|-----------------------------|------|
| Condensing Unit Size (H.P.) | 1/2 |
| Capacity (BTU per hour)* | 1590 |

ELECTRICAL DATA

| | |
|--|---------------------|
| Voltage (International) | 115/60/1 (220/50/1) |
| Feed Wires (including ground) | 3 |
| Total Amps (International) | 7.6 (4.2) |
| Defrost Amps (International) | 3.7 (2.0) |
| 10 ft. Cord/Plug [attached] (International) | Yes (No) |

SHIPPING DATA



| | |
|------------------------------|------------------|
| Height - Crated (inches) | 85 1/2 (2172 mm) |
| Width - Crated (inches) | 32 (813 mm) |
| Depth - Crated (inches) | 42 (1067 mm) |
| Volume - Crated (cubic feet) | 65 (1841 cu l) |
| Weight Std - Crated (pounds) | 300 (136 kg) |
| Weight SS - Crated (pounds) | 320 (145 kg) |

* Rating @ -15°F evaporator, 90°F ambient
 Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug
 (varies by country)

Model Plan Views



IMPORTANT NOTE: If the cabinet is located directly against a wall and/or under a low ceiling, a minimum clearance of 12" is required on top and 3" on sides and rear.



Toll-Free: 800-523-7138
 Phone: 215-244-1400
 Fax: 215-244-9579

539 Dunksferry Road
 Bensalem, PA 19020
www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.

