

# DISPLAY FREEZER (0°F)

## Model: 2FNGD

Natural Refrigerant R-290 Model

### 2-Section Display Reach-In Freezer with Hinged Glass Doors

- 2FNGD** - Stainless steel front, aluminum end panels and interior
- 2FNSAGD** - Stainless steel exterior, aluminum interior
- 2FNSSGD** - Stainless steel exterior and interior



## Options and Accessories

(upcharge and lead times may apply)

|                                       |   |
|---------------------------------------|---|
| Stainless steel case back             | Special electrical requirements (consult factory) |
| Additional epoxy coated steel shelves | Shallow depth (consult factory)                   |
| Chrome or stainless steel shelves     | Solid door (consult factory)                      |
| Heavy duty pilaster strips            | Half doors  |
| Wine rack                             | Rehinging of doors (consult factory)              |
| Adjustable legs                       | Pass thru (consult factory)                       |
| Pan slide assemblies                  |   |

Consult factory for other model configurations, options and accessories.

**Continental**  
Refrigerator



Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

## Standard Model Features

### REFRIGERATION SYSTEM

Self contained, performance rated refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant<sup>1</sup>

Automatic, electric condensate evaporator

Expansion valve system

Standard operating temperature is 0 to -5°F and can be adjusted to operate as low as -10°F in a 90°F ambient.

### CABINET ARCHITECTURE

3" non-CFC polyurethane foam insulation

Triple-pane, tempered hinged glass doors

Chrome plated door handles

Cam action, lift-off hinges

Self-closing doors

Magnetic snap in door gaskets

Cylinder lock in each door

Heavy duty, epoxy coated steel shelves

5" casters

### MODEL FEATURES

LED interior lighting

Electronic control, automatic electric defrost

<sup>1</sup> R-290 refrigerant meets all federal and state regulatory requirements.

APPROVAL:

## Model Specifications

### DIMENSIONAL DATA

|  |                  |
|--|------------------|
| Net Capacity (cubic feet)                          | 48 (1359 cu l)   |
| Width, Overall (inches)                            | 52 (1321 mm)     |
| Depth, Overall (inches)<br>(including handles)     | 35 3/8 (899 mm)  |
| Depth (inches) (less doors)                        | 32 (813 mm)      |
| Depth (inches) (doors open 90°)                    | 55 1/2 (1410 mm) |
| Clear Door Width (inches)                          | 19 3/8 (492 mm)  |
| Clear Door Height (inches)                         | 58 5/8 (1489 mm) |
| Height, Overall (inches)<br>(including 5" casters) | 82 1/4 (2089 mm) |
| Number of Doors                                    | 2                |
| Number of Shelves                                  | 8                |
| Shelf Area (square feet)                           | 40.8 (3.8 sq m)  |
| Tray Slide Capacity (per section)<br>(2" centers)  | 24               |

### REFRIGERANT DATA

|                             |       |
|-----------------------------|-------|
| Condensing Unit Size (H.P.) | 1 1/4 |
| Capacity (BTU per hour)*    | 4325  |

### ELECTRICAL DATA

|                                  |                                |
|----------------------------------|--------------------------------|
| Voltage<br>(International)       | 115/208-230/60/1<br>(220/50/1) |
| Feed Wires (with ground)         | 4                              |
| Total Amps (International)       | 10.8 (5.3)                     |
| Defrost Amps (International)     | 6.1 (3.1)                      |
| 10 ft. Cord/Plug (International) | Yes (No)                       |



### SHIPPING DATA

|                              |                  |
|------------------------------|------------------|
| Height - Crated (inches)     | 85 1/2 (2172 mm) |
| Width - Crated (inches)      | 64 (1626 mm)     |
| Depth - Crated (inches)      | 42 (1067 mm)     |
| Volume - Crated (cubic feet) | 133 (3766 cu l)  |
| Weight Std - Crated (pounds) | 504 (229 kg)     |
| Weight SS - Crated (pounds)  | 605 (275 kg)     |

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.

\* Rating @ -15°F evaporator, 90°F ambient

## Model Plan Views



**IMPORTANT NOTE:** If the cabinet is located directly against a wall and/or under a low ceiling, a minimum clearance of 12" is required on top and 3" on sides and rear.

**Continental**  
Refrigerator


Toll-Free: 800-523-7138  
Phone: 215-244-1400  
Fax: 215-244-9579

539 Dunksferry Road  
Bensalem, PA 19020  
[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

Due to our continued efforts in developing innovative products, specifications subject to change without notice.



PROUDLY  
DESIGNED & ASSEMBLED  
IN THE U.S.A.



Equipped with one NEMA L14-20P plug  
(varies by country)

© Copyright 2021. Continental Refrigerator.  
A Division of National Refrigeration & Air Conditioning Products, Inc.

REVISED: 3/29/24