# **DESIGNER LINE REFRIGERATOR/FREEZER**

## **Model: D2RFENHD**

Natural Refrigerant R-290 Model



2-Section Extra-Wide Dual Temp Side-By-Side Reach-In Refrigerator/ Freezer (0°F) with Half Doors

**D2RFENHD** - Stainless steel front, aluminum end panels and interior **D2RFENSAHD** - Stainless steel exterior, aluminum interior

D2RFENSSHD - Stainless steel exterior and interior



### **Options and Accessories**

(upcharge and lead times may apply)

Stainless steel case back	Hinged glass doors (consult factory)	
Additional epoxy coated steel shelves	Special electrical req. (consult factory)	
Chrome or stainless steel shelves	Correctional Facility Options	
Rehinging of doors (consult factory)	One way security screws	
Universal pan slides	Locking hasp (lock not included)	
Wine rack	Stainless steel mesh cover	
Casters	Coverless hinges	
Custom laminates		

Consult factory for other model configurations, options and accessories.





Project Name:	
Model Specified:	
Location:	
Item No:	Quantity:
AIA #:	SIS #:

## **Standard Model Features**

#### **REFRIGERATION SYSTEM**

Separate, self contained, performance rated "plug" refrigeration systems

Natural, environmentally safe, high efficiency R-290 refrigerant<sup>1</sup>

Refrigeration system is readily accessible on top of cabinet, separate from the "food zone"

Automatic, hot gas condensate evaporator

Expansion valve system

#### **CABINET ARCHITECTURE**

3" non-CFC polyurethane foam insulation

Smooth, polished chrome workflow door handles

Cam action, lift off hinges

Self-closing doors

Magnetic snap in Santoprene™ door gaskets

Cylinder lock in each door

Heavy duty, epoxy coated steel shelves

Heavy duty pilaster strips

6" adjustable stainless steel legs

#### **MODEL FEATURES**

LED interior lighting

Electronic controllers with digital display & hi-low alarm

Top and side air distribution ducts

Cabinet upper side panels and refrigeration "plug" system can be removed and reinstalled at job site

Off-cycle defrost (refrigerator section)

Automatic electric defrost (freezer section)

APPROVAL:

# **Model Specifications**

DIMENSIONAL DATA	
Net Capacity (cubic feet)	21/21 (595/595 cu I)
Width, Overall (inches)	57 (1448 mm)
Depth, Overall (inches) (including handles)	35 3/8 (899 mm)
Depth (inches) (less doors)	32 (813 mm)
Depth (inches) (doors open 90°)	58 (1473 mm)
Clear Door Width (inches)	21 7/8 (556 mm)
Clear Half Door Height (inches)	27 1/2 (699 mm)
Height, Overall (inches) (including 5" casters)	83 1/4 (2089 mm)
Number of Doors	4
Number of Shelves	6
Shelf Area (square feet) (per section)	20.4 (1.9 sq m)
Tray Slide Capacity (per half section)	11
REFRIGERANT DATA	
Condensing Unit Size (H.P.)	1/4, 1/2
Capacity (BTU per hour)*	1940 / 1590
ELECTRICAL DATA	
Voltage (International)	115/60/1 (220/50/1)
Feed Wires (including ground)	3/3
Total Amps (International)	5.1 (3.7) / 6.5 (4.1)
Defrost Amps (International)	4.3 (2.2)

#### (International) SHIPPING DATA

(2) 10 ft. Cord/Plug [attach.]

85 1/2 (2172 mm)
64 (1626 mm)
42 (1067 mm)
133 (3766 cu I)
590 (268 kg)
705 (320 kg)

Yes

(No)


- $^{\star}$  Rating @ +25°F evaporator, 90°F ambient (refrigerator)  $^{\star}$  Rating @ -15°F evaporator, 90°F ambient (freezer)


Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.

Equipped with two NEMA-5-15P Plugs (varies by country)

### **Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579 539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com Refrigerator Due to our continued efforts in developing innovative products, specifications subject to change without notice. PROUDLY DESIGNED & ASSEMBLED IN THE U.S.A. Intertek © Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

# **Model Plan Views**





**IMPORTANT NOTE**: If the cabinet is located directly against a wall and/or under a low ceiling, a minimum clearance of 12" is required on top and 3" on sides and rear.