DESIGNER LINE ROLL-IN REFRIGERATOR

Model: D2RIN

Natural Refrigerant R-290 Model



2-Section Roll-In Refrigerator with 661/4" Cart Capacity



ENERGY STAR® Qualified Commercial Refrigerator

D2RIN - Stainless steel front, aluminum end panels and interior

D2RINSA - Stainless steel exterior, aluminum interior **D2RINSS** - Stainless steel exterior and interior



Options and Accessories

(upcharge and lead times may apply)

| (| |
|--------------------------------------|---|
| Epoxy coated steel shelves | Special electrical req. (consult factory) |
| Chrome or stainless steel shelves | Correctional Facility Options |
| Rehinging of doors (consult factory) | One way security screws |
| Custom laminates | Locking hasp (lock not included) |
| Half doors | Stainless steel mesh cover |
| Stainless steel back | Coverless hinges |

Consult factory for other model configurations, options and accessories.

| Project Name: | | |
|------------------|-----------|--|
| Model Specified: | | |
| Location: | | |
| Item No: | Quantity: | |
| | | |
| AIA #: | SIS #: | |

Standard Model Features

REFRIGERATION SYSTEM

Self contained, performance rated "plug" refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant¹

Refrigeration system is readily accessible on top of cabinet, separate from the "food zone"

Automatic, hot gas condensate evaporator

Expansion valve system

CABINET ARCHITECTURE

3" non-CFC polyurethane foam insulation

Smooth, polished chrome workflow door handles

Cam action, lift off hinges

Magnetic snap in Santoprene™ door gaskets

Cylinder lock in each door

Self-closing doors

66 ½" high door opening (66 ¼"H rack capacity*)

MODEL FEATURES

Electronic control, off cycle defrost

LED interior lighting

Top and side air distribution ducts

Cabinet upper side panels and refrigeration "plug" system can be removed and reinstalled at job site

Removable stainless steel rack guides

Removable stainless steel ramps

Reinforced stainless steel floor

* Rack not supplied

IMPORTANT NOTE: ¹ R-290 refrigerant meets all federal and state regulatory requirements.





APPROVAL:

Model Specifications

DIMENSIONAL DATA Net Capacity (cubic feet) 64 (1812 cu I) Width, Overall (inches) 68 ½ (1740 mm) Depth, Overall (inches) 35 3/8 (899 mm) (including handles) Depth (inches) (less doors) 32 (813 mm) Depth (inches) (doors open 90°) 65 (1651 mm) Clear Door Width (inches) 27 3/8 (695 mm) Clear Full Door Height (inches) 66 ½ (1676 mm) 86 (2184 mm) Height, Overall (inches) 2 Number of Door(s) Rack Capacity** 2

REFRIGERANT DATA

| Condensing Unit Size (H.P.) | 1/2+ |
|-----------------------------|------|
| Capacity (BTU per hour)* | 4010 |

^{*} Rating @ +25°F evaporator, 90°F ambient

ELECTRICAL DATA

| Voltage (International) | 115/60/1 (220/50/1) |
|---|---------------------|
| Feed Wires (including ground) | 3 |
| Total Amps (International) | 9.4 (4.2) |
| 10 ft. Cord/Plug [attached] (International) | Yes (No) |

SHIPPING DATA

| Height - Crated (inches) | 94 (2288 mm) |
|------------------------------|-----------------|
| Width - Crated (inches) | 77 (1956 mm) |
| Depth - Crated (inches) | 42 (1067 mm) |
| Volume - Crated (cubic feet) | 168 (4757 cu I) |
| Weight Std - Crated (pounds) | 634 (288 kg) |
| Weight SS - Crated (pounds) | 665 (302 kg) |

^{*} Rating @ +25°F evaporator, 90°F ambient

^{**} Maximum rack size including wheels - 27"W x 29"D x 66 $^{1}\!4$ "H Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug (varies by country)

Continental® Refrigerator

Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.









 $\@$ Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

Model Plan Views





IMPORTANT NOTE: If the cabinet is located directly against a wall and/or under a low ceiling, a <u>minimum</u> clearance of 12" is required on top and 3" on sides and rear.