# **DESIGNER LINE REFRIGERATOR/FREEZER**

**Model: D3RRFNPTHD** 

Natural Refrigerant R-290 Model



3-Section Dual Temp Side-By-Side Pass-Thru Refrigerator/Freezer (0°F) with Half Doors

**D3RRFNPTHD** - Stainless steel front, aluminum end panels and interior **D3RRFNSAPTHD** - Stainless steel exterior, aluminum interior

D3RRFNSSPTHD - Stainless steel exterior and interior




### **Options and Accessories**

(upcharge and lead times may apply)

Additional epoxy coated steel shelves	Increased refrigeration systems
Chrome or stainless steel shelves	Special electrical req. (consult factory)
Pan slide assemblies	Correctional Facility Options
Rehinging of doors (consult factory)	One way security screws
Wine rack (refrigerator section)	Locking hasp (lock not included)
Casters	Stainless steel mesh cover
Custom laminates	Coverless hinges

Consult factory for other model configurations, options and accessories.



### **Standard Model Features**

#### **REFRIGERATION SYSTEM**

Separate, self contained, performance rated "plug" refrigeration systems

Natural, environmentally safe, high efficiency R-290 refrigerant<sup>1</sup>

Refrigeration system is readily accessible on top of cabinet, separate from the "food zone"

Automatic, hot gas condensate evaporator

Expansion valve system

#### **CABINET ARCHITECTURE**

3" non-CFC polyurethane foam insulation

Smooth, polished chrome workflow door handles

Cam action, lift off hinges

Self-closing doors

Magnetic snap in Santoprene™ door gaskets

Cylinder lock in each door

Heavy duty, epoxy coated steel shelves

Heavy duty pilaster strips

6" adjustable stainless steel legs

### **MODEL FEATURES**

LED interior lighting

Electronic controllers with digital display & hi-low alarm

Top and side air distribution ducts

Cabinet upper side panels and refrigeration "plug" system can be removed and reinstalled at job site

Off-cycle defrost (refrigerator section)

Automatic electric defrost (freezer section)





APPROVAL:

# **Model Specifications**

DIMENSIONAL DATA	
Net Capacity (cubic feet)	50, 21 (1416, 595 cu l)
Width, Overall (inches)	78 (1981 mm)
Depth, Overall (inches) (including handles)	38 3/4 (984 mm)
Depth (inches) (less doors)	32 (813 mm)
Depth (inches) (doors open 90°)	79 (2007 mm)
Clear Door Width (inches)	19 3/8 (492 mm)
Clear Door Height (inches)	58 5/8 (1489 mm)
Height, Overall (inches) (including 6" legs)	83 1/4 (2115 mm)
Number of Doors	6
Number of Shelves	9
Shelf Area (square feet) (per section)	20.4 (1.9 sq m)
Tray Slide Capacity (per section)	24
REFRIGERANT DATA	
Condensing Unit Size (H.P.)	1/3 +, 1/2
Capacity (BTU per hour)*	2560, 1590
ELECTRICAL DATA	
Voltage (International)	115/60/1 (220/50/1)
Feed Wires (including ground)	3, 3
Total Amps (International)	6.4 (4.7), 6.9 (4.2)
Defrost Amps (International)	4.3 (2.2)
(2) 10 ft. Cord/Plug [attach.] (International)	Yes (No)
SHIPPING DATA	
Height - Crated (inches)	85 1/2 (2172 mm)
Width - Crated (inches)	90 (2286 mm)
Depth - Crated (inches)	42 (1067 mm)

- \* Rating @ +25°F evaporator, 90°F ambient (refrigerator)
- \* Rating @ -15°F evaporator, 90°F ambient (freezer)

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.

Volume - Crated (cubic feet)

Weight Std - Crated (pounds)

Weight SS - Crated (pounds)

Equipped with two NEMA-5-15P Plugs (varies by country)

## Refrigerator Due to our continued efforts in developing innovative products, specifications subject to change without notice.

**Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

187 (5295 cu I)

825 (374 kg) 935 (424 kg)

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com









© Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

### **Model Plan Views**





IMPORTANT NOTE: If the cabinet is located under a low ceiling, a minimum clearance of 12" is required on top and 3" on sides.