# DESIGNER LINE SANDWICH UNIT

<u>Designer line</u>

Model: D72N24M-FB Natural Refrigerant R-290 Model

## 72" Mighty Top Sandwich Unit Refrigerator with Solid Door - 24 Pans Front Breathing

Stainless steel front, top and end panels and interior.



### **Options and Accessories**

| (upcharge and lead times may apply)   |                            |  |
|---------------------------------------|----------------------------|--|
| Stainless steel back                  | Drawers in lieu of doors** |  |
| Overshelves (single or double)        | Rear mounted cutting board |  |
| Additional epoxy coated steel shelves | Composite cutting board    |  |
| Stainless steel shelves               | Flat insulated night cover |  |
| Door lock                             | Vision panel lid           |  |
| Crumb catcher                         | Modified pan openings      |  |

Consult factory for other model configurations, options and accessories. \*\*Two-Tier Drawers Accommodate: (1)  $12 \times 18 \times 6$  pan per drawer OR (1)  $1/2 \times 6$  AND (1)  $1/3 \times 6$  pans per drawer





| Project Name:    |           |
|------------------|-----------|
|                  |           |
| Model Specified: |           |
|                  |           |
| Location:        |           |
|                  |           |
| Item No:         | Quantity: |
|                  |           |
| AIA #:           | SIS #:    |

## **Standard Model Features**

#### **REFRIGERATION SYSTEM**

| Performance rated refrigeration system   |
|--|
| Natural, environmentally safe,<br>high efficiency R-290 refrigerant <sup>1</sup> |
| Unique air flow distribution allows<br>pan product to maintain 33° - 41°F        |
| Automatic, hot gas condensate evaporator   |
| Non-corrosive, plasticized fin evaporator coil                                   |
| Expansion valve system   |
| Easily serviceable, back mounted compressor                                      |

#### **CABINET ARCHITECTURE**

| 2" non-CFC polyurethane foam insulation             |  |
|---|--|
| Smooth, polished chrome door handles                |  |
| Spring loaded, self closing doors                   |  |
| Magnetic snap in Santoprene™ door gaskets           |  |
| Heavy duty, epoxy coated steel shelves              |  |
| 8" deep, full length nylon cutting board            |  |
| Insulated lid                                       |  |
| Completely enclosed, vented and removable case back |  |
| 3 ¾" Casters  |  |

#### **MODEL FEATURES**

| Electronic control, off cycle defrost                        |
|--|
| (24) <sup>1</sup> / <sub>6</sub> size recessed pans, 4" deep |
| Removable interior tub below pans                            |
| Field rehingeable doors                                      |

<sup>1</sup> R-290 refrigerant meets all federal and state regulatory requirements.

APPROVAL:

## **Model Specifications**

| DIMENSIONAL DATA  |                 |
|---|-----------------|
| Net Capacity (cubic feet)   | 20.6 (583 cu l) |
| <sup>1</sup> / <sub>6</sub> Size Pans (4" deep)                                 | 24              |
| Width, Overall (inches)   | 72 (1829 mm)    |
| Depth, Overall (inches)<br>(including bumpers)                                  | 35 (890 mm)     |
| Depth, Cutting Board (inches)   | 8 (203 mm)      |
| Height, Overall (inches)<br>(including 3 <sup>3</sup> / <sub>4</sub> " casters) | 41 (1041 mm)    |
| Shelf Area (square feet)  | 10.2 (0.9 sq m) |
| Number of Shelves   | 3               |
| Number of Doors   | 3               |
| Interior Depth (inches)   | See Drawing     |
| Interior Height (inches)  | 26 ¼ (667 mm)   |
| Interior Width (inches)   | 68 (1727 mm)    |
|   |                 |

#### **REFRIGERANT DATA**

| Condensing Unit Size (H.P.) |  |
|-----------------------------|--|
| Capacity (BTU per hour)*    |  |

#### **ELECTRICAL DATA**

| Voltage (International)                        | 115/60/1 (220/50/1) |
|--|---------------------|
| Total Amps (International)                     | 6.0 (3.6)           |
| 10 ft. Cord/Plug [attached]<br>(International) | Yes<br>(No)         |

1/3+

2560

#### **SHIPPING DATA**

| Weight (pounds)          | 445 (202 kg)   |
|--------------------------|----------------|
| Height - Crated (inches) | 43 ¼ (1099 mm) |
| Width - Crated (inches)  | 80 (2032 mm)   |
| Depth - Crated (inches)  | 37 ¼ (946 mm)  |

\* Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



## **Model Plan Views**





