SHALLOW DEPTH BASE MODEL REFRIGERATOR

Model: RA43SNBS-D

Natural Refrigerant R-290 Model

43" Shallow Depth Worktop Refrigerator with Drawers and 5.5" Backsplash



ENERGY STAR® Qualified Commercial Refrigerator

Heavy gauge #300 series stainless steel top, stainless steel front and end panels, galvanized steel rear and grills and aluminum interior.



Options and Accessories

(upcharge and lead times may apply)

| Stainless steel interior | Condensing unit left (standard on right) |
|--------------------------------|--|
| Stainless steel back | Adjustable legs |
| Overshelves (single or double) | Front Breathing |
| Door & drawer locks | |

Consult factory for other model configurations, options and accessories.

*Drawer section above condensing unit holds (4) 1/6 pans

Drawer in lieu of door section above the condensing unit*





| Project Name: | |
|------------------|-----------|
| | |
| Model Specified: | |
| Location: | |
| Location. | |
| Item No: | Quantity: |
| | |
| AIA #: | SIS #: |

Standard Model Features

REFRIGERATION SYSTEM

Performance rated refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant¹

Unique forced air design utilizes fans (approx. every 12") across the entire back of unit for even distribution of cold

Automatic, hot gas condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, slide out condensing unit

Expansion valve system

CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation

Smooth, polished chrome door & drawer handles

Spring loaded, self closing door over condensing unit

Magnetic snap in Santoprene™ door gaskets

Completely enclosed, vented, and removable rear and side grill

5" casters

Stainless steel roll out drawers

MODEL FEATURES

Refrigerated section with door above the condensing unit

Electronic control, off-cycle defrost

Field rehingeable door over condensing unit

¹ R-290 refrigerant meets all federal and state regulatory requirements.

NOTE: Models come standard with a door above the condensing unit. A drawer above the condensing unit is an option.

APPROVAL:

Model Specifications

| DIMENSIONAL DATA | |
|---|-----------------|
| Net Capacity (cubic feet) | 9.6 (272 cu I) |
| Width, Overall (inches) | 43 (1092 mm) |
| Depth, Overall (inches) (including handles & bumpers) | 31 (770 mm) |
| Height, Overall (inches) (including 5" casters) | 40.5 (1029 mm) |
| Number of Drawers | 2 |
| Number of Half Doors | 1 |
| Interior Depth (inches) | 24 (610 mm) |
| Interior Height (inches) | 12 1/2 (318 mm) |

REFRIGERANT DATA

| Condensing Unit Size (H.P.) | 1/4 |
|-----------------------------|------|
| Capacity (BTU per hour)* | 2260 |

ELECTRICAL DATA

| Voltage (International) | 115/60/1 (220/50/1) |
|---|---------------------|
| Total Amps (International) | 3.38 (1.63) |
| 10 ft. Cord/Plug [attached] (International) | Yes (No) |

SHIPPING DATA

| Weight (pounds) | 265 (120 kg) |
|--------------------------|------------------|
| Height - Crated (inches) | 43 3/4 (1111 mm) |
| Width - Crated (inches) | 45 (1143 mm) |
| Depth - Crated (inches) | 47 (1194 mm) |

DRAWER PAN CONFIGURATIONS

Two Tier: (1) 12x20x6 pans per drawer

* Rating @ +25°F evaporator, 90°F ambient Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug (varies by country)

Refrigerator

Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.







Intertek

© Copyright 2021. Continental Refrigerator.

A Division of National Refrigeration & Air Conditioning Products, Inc.

Model Plan Views



