BASE MODEL SANDWICH UNIT

Model: RA60N8

Natural Refrigerant R-290 Model

60" Standard Top Sandwich Unit Refrigerator with Solid Doors - 8 Pans

Heavy gauge #300 series stainless steel top, stainless steel front and end panels, galvanized steel rear and grills and aluminum interior.



Options and Accessories

(upcharge and lead times may apply)		
Stainless steel interior	Flat lid	
Stainless steel back	Vision panel lid	
Additional epoxy coated steel shelves	Door locks	
Stainless steel shelves	Front breathing	
Overshelves (single or double)	Rear mounted cutting board	
Adjustable legs	Composite cutting board	
Pan slides (large section only)	Compressor left (standard on right)	
Drawers in lieu of doors**		

Drawer in lieu of door section above the condensing unit*

Consult factory for other model configurations, options and accessories. *Drawer section above condensing unit holds (1) 12 x 20 x 6 pan.

 $^{*}{}^{\rm Two}$ tier (larger section): TOP: (1) 12x20x6 AND (3) 1/6 x 6 BOTTOM: (2) 12x20x6 pans

**Two Narrow: (1) 12x20x6 pan per drawer





Project Name:	
Model Specified:	
I anotion.	
Location:	
Item No:	Quantity:
A1A #.	010 #.
AIA #:	SIS #:

Standard Model Features

REFRIGERATION SYSTEM

Performance rated refrigeration systemNatural, environmentally safe,
high efficiency R-290 refrigerant1Unique forced air design utilizes fans (approx. every 12")
across the entire back of unit for even distribution of coldAutomatic, hot gas condensate evaporatorNon-corrosive, plasticized fin evaporator coilEasily serviceable, slide out condensing unitExpansion valve system

CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation	
Smooth, polished chrome door handles	
Spring loaded, self closing doors	
Magnetic snap in Santoprene [™] door gaskets	
Heavy duty, epoxy coated steel shelves	
12" deep, full length nylon cutting board	
Insulated lid	
5" casters	

MODEL FEATURES

Refrigerated section with door above the condensing unit
(8) $1/6$ size recessed pans, 4" deep
Electronic control, off-cycle defrost

Field rehingeable doors

¹ R-290 refrigerant meets all federal and state regulatory requirements.

NOTE: Models come standard with a door above the condensing unit. A drawer above the condensing unit is an option.

APPROVAL:

Model Specifications

DIMENSIONAL DATA

Net Capacity (cubic feet)	19 (538 cu l)
1/6 Size Pans (4" deep)	8
Width, Overall (inches)	60 (1524 mm)
Depth, Overall (inches) (including handles & bumpers)	37 (940 mm)
Depth, Cutting Board (inches)	12 (305 mm)
Height, Overall (inches) (including 5" casters)	42 (1067 mm)
Shelf Area (square feet)	7.1 (0.7 sq m)
Number of Shelves	4
Number of Full Doors	2
Number of Half Doors	1
Interior Depth (inches)	30 (762 mm)
Interior Height (inches)	26 (660 mm)
Interior Height (inches) (above condenser)	12 1/2 (318 mm)
Interior Width (inches)	56 (1422 mm)

REFRIGERANT DATA

Condensing Unit Size (H.P.)	1/3+
Capacity (BTU per hour)*	2600

ELECTRICAL DATA

Voltage (International)	115/60/1 (220/50/1)
Total Amps (International)	5.8 (3.9)
10 ft. Cord/Plug [attached] (International)	Yes (No)

SHIPPING DATA

Weight (pounds)	420 (191 kg)
Height - Crated (inches)	43 3/4 (1111 mm)
Width - Crated (inches)	62 (1575 mm)
Depth - Crated (inches)	47 (1194 mm)

* Rating @ +25°F evaporator, 90°F ambient Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug (varies by country)



© Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

Model Plan Views





