# SHALLOW DEPTH BASE MODEL REFRIGERATOR

## Model: RA68SNBS-D

Natural Refrigerant R-290 Model

68" Shallow Depth Worktop

Refrigerator with Drawers and 5.5" Backsplash



ENERGY STAR® Qualified Commercial Refrigerator

Heavy gauge #300 series stainless steel top, stainless steel front and end panels, galvanized steel rear and grills and aluminum interior.



### **Options and Accessories**

(upcharge and lead times may apply)

Adjustable legs	Front breathing
	Overshelves (single or double)

Consult factory for other model configurations, options and accessories.
\*Drawer section above condensing unit holds (4) 1/6 pans





Project Name:	
Model Specified:	
Location:	
Location.	
Item No:	Quantity:
	·
AIA #:	SIS #:

## **Standard Model Features**

#### **REFRIGERATION SYSTEM**

Performance rated refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant<sup>1</sup>

Unique forced air design utilizes fans (approx. every 12") across the entire back of unit for even distribution of cold

Automatic, hot gas condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, slide out condensing unit

Expansion valve system

#### **CABINET ARCHITECTURE**

2" non-CFC polyurethane foam insulation

Smooth, polished chrome door & drawer handles

Spring loaded, self closing door over condensing unit

Magnetic snap in Santoprene™ door gaskets

Stainless steel roll out drawers

Completely enclosed, vented and removable rear and side grills

5" casters

#### **MODEL FEATURES**

Refrigerated section with door above the condensing unit

Electronic control, off-cycle defrost

Field rehingeable door over condensing unit

<sup>1</sup> R-290 refrigerant meets all federal and state regulatory requirements.

**NOTE:** Models come standard with a door above the condensing unit. A drawer above the condensing unit is an option.

APPROVAL:

## **Model Specifications**

DIMENSIONAL DATA	
Net Capacity (cubic feet)	17.6 (498 cu l)
Width, Overall (inches)	68 (1732 mm)
Depth, Overall (inches) (including handles & bumpers)	31 (770 mm)
Height, Overall (inches) (including 5" casters)	40.5 (1029 mm)
Number of Drawers	4
Number of Half Doors	1
Interior Depth (inches)	24 (610 mm)
Interior Height (inches) (above condenser)	12 1/2 (318 mm)
REFRIGERANT DATA	
Condensing Unit Size (H.P.)	1/4+
Capacity (BTU per hour)*	4220
ELECTRICAL DATA	
Voltage (International)	115/60/1 (220/50/1)
Total Amps (International)	4.2 (2.9)
10 ft. Cord/Plug [attached] (International)	Yes (No)
SHIPPING DATA	
Weight (pounds)	380 (172 kg)
Height - Crated (inches)	43 3/4 (1111 mm)

#### **DRAWER PAN CONFIGURATIONS**

**Two Tier**: (1) 12 x 20 x 6 pan per drawer (supplied by others)

Width - Crated (inches)

Depth - Crated (inches)

\* Rating @ +25°F evaporator, 90°F ambient
Figures in parentheses reflect metric equivalents rounded to the nearest whole unit



Equipped with one NEMA-5-15P Plug (varies by country)



**Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

70 (1778 mm)

47 (1194 mm)

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.







#### Intertek

© Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

## **Model Plan Views**



