
SANDWICH UNIT REFRIGERATOR

Model: SW27N8-D

Natural Refrigerant R-290 Model

27" Standard Top Sandwich Unit Refrigerator with Drawers - 8 Pans

Stainless steel front, top and end panels, aluminum back and interior.





Options and Accessories

(upcharge and lead times may apply)

| Stainless steel interior | Drawer locks |
|--------------------------------|----------------------------|
| Stainless steel back | Front breathing |
| Overshelves (single or double) | Rear mounted cutting board |
| Adjustable legs | Composite cutting board |
| Optional caster sizes | Crumb catcher |
| Flat lid | Modified pan opening |
| Vision panel lid | |
| | |

Consult factory for other model configurations, options and accessories.





Standard Model Features

REFRIGERATION SYSTEM

Performance rated refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant¹

Unique air flow distribution allows pan product to maintain 33° - 41°F

Automatic, hot gas condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, back mounted compressor

CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation

Smooth, polished chrome drawer handles

Stainless steel roll out drawers

Magnetic snap in Santoprene™ drawer gaskets

12" deep, full length nylon cutting board

Insulated lid

Completely enclosed, vented and removable case back

5" casters

MODEL FEATURES

Electronic control, off-cycle defrost
(8) 1/6 size recessed pans, 4" deep
Off-cycle defrost
Removable interior tub below pans

¹ R-290 refrigerant meets all federal and state regulatory requirements.



Model Specifications

| DIMENSIONAL DATA | |
|--|------------------|
| Net Capacity (cubic feet) | 7.4 (210 cu l) |
| 1/6 Size Pans (4" deep) | 8 |
| Width, Overall (inches) | 27 1/2 (699 mm) |
| Depth, Overall (inches) (including handles & bumpers) | 32 5/16 (821 mm) |
| Depth, Cutting Board (inches) | 12 (305 mm) |
| Height, Overall (inches) (including 5" casters) | 42 1/4 (1073 mm) |

2

REFRIGERANT DATA

Number of Drawers (two tier)

| Condensing Unit Size (H.P.) | 1/5 | |
|-----------------------------|------|--|
| Capacity (BTU per hour)* | 1625 | |

^{*} Rating @ +25°F evaporator, 90°F ambient

ELECTRICAL DATA

| Voltage (International) | 115/60/1 (220/50/1) |
|---|---------------------|
| Total Amps (International) | 2.46 (1.85) |
| 10 ft. Cord/Plug [attached] (International) | Yes (No) |

SHIPPING DATA

| Weight (pounds) | 180 (82 kg) |
|--------------------------|------------------|
| Height - Crated (inches) | 43 1/4 (1099 mm) |
| Width - Crated (inches) | 35 1/2 (902 mm) |
| Depth - Crated (inches) | 37 1/4 (946 mm) |

DRAWER PAN CONFIGURATIONS

Two Tier: (1) 12 x 20 x 6 pan per drawer

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug (varies by country)

Continental® Refrigerator

Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.







 \circledcirc Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

Model Plan Views

