# SANDWICH UNIT REFRIGERATOR

# Model: SW27N8-FB

Natural Refrigerant R-290 Model

### 27" Standard Top Sandwich Unit Refrigerator with Solid Door - 8 Pans Front Breathing

Stainless steel front, top and end panels, aluminum back and interior.



### **Options and Accessories**

(upcharge and lead times may apply)		
Stainless steel interior	Flat lid	
Stainless steel back	Vision panel lid	
Additional epoxy coated steel shelves	Rear mounted cutting board	
Stainless steel shelves	Composite cutting board	
Overshelves (single or double)	Crumb catcher	
Door locks	Modified pan opening	
Drawers in lieu of door*		

Consult factory for other model configurations, options and accessories. \*Drawers hold (1) 12x20x6 pan per drawer.





Project Name:	
Model Specified:	
Location:	
Item No:	Quantity:
AIA #:	SIS #:

## **Standard Model Features**

#### **REFRIGERATION SYSTEM**

Performance rated refrigeration system Natural, environmentally safe, high efficiency R-290 refrigerant<sup>1</sup> Unique air flow distribution allows pan product to maintain 33° - 41°F Automatic, hot gas condensate evaporator Non-corrosive, plasticized fin evaporator coil Easily serviceable, back mounted compressor

#### **CABINET ARCHITECTURE**

2" non-CFC polyurethane foam insulation
Smooth, polished chrome door handle
Spring loaded, self closing door
Magnetic snap in Santoprene <sup>™</sup> door gasket
Heavy duty, epoxy coated steel shelf
12" deep, full length nylon cutting board
Insulated lid
Completely enclosed, vented and removable case back
3 3/4" casters

### **MODEL FEATURES**

(8) 1/6 size recessed pans, 4" deep
Removable interior tub below pans
Electronic control, off-cycle defrost
Field rehingeable door

<sup>1</sup> R-290 refrigerant meets all federal and state regulatory requirements.

Front breathers are a unique, field assembled, bottom mounted ventilation system designed to allow cabinets to be flush against a wall or built into a counter to conserve space. For proper operation, the area under and in front of the cabinet <u>must</u> not be obstructed in any way.

APPROVAL:

### **Model Specifications**

#### **DIMENSIONAL DATA** Net Capacity (cubic feet) 7.4 (210 cu l) 1/6 Size Pans (4" deep) 8 Width, Overall (inches) 27 1/2 (699 mm) Depth, Overall (inches) 32 3/16 (818 mm) (including handle & bumpers) Depth, Cutting Board (inches) 12 (305 mm) Height, Overall (inches) 41 (1041 mm) (including 3 3/4" casters) Shelf Area (square feet) 3.5 (0.3 sq m) Number of Shelves 1 Number of Doors 1 Interior Depth (inches) See Drawing Interior Height (inches) 26 1/4 (667 mm) Interior Width (inches) 24 1/2 (622 mm)

#### **REFRIGERANT DATA**

Condensing Unit Size (H.P.)	
Capacity (BTU per hour)*	

#### **ELECTRICAL DATA**

Voltage (International)	115/60/1 (220/50/1)
Total Amps (International)	2.46 (1.85)
10 ft. Cord/Plug [attached] (International)	Yes (No)

1/5

1625

FRONT VIEW

#### **SHIPPING DATA**

Weight (pounds)	230 (105 kg)
Height - Crated (inches)	43 1/4 (1099 mm)
Width - Crated (inches)	35 1/2 (902 mm)
Depth - Crated (inches)	37 1/4 (946 mm)

\* Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



### **Model Plan Views**





