SANDWICH UNIT REFRIGERATOR

Model: SW32N12M-D

Natural Refrigerant R-290 Model

32" Mighty Top Sandwich Unit Refrigerator with Drawers - 12 Pans

Stainless steel front, top and end panels, aluminum back and interior.



Options and Accessories

(upcharge and lead times may apply)		
Stainless steel interior	Drawer locks	
Stainless steel back	Front breathing	
Overshelves (single or double)	Rear mounted cutting board	
Adjustable legs	Composite cutting board	
Optional caster sizes	Crumb catcher	
Flat lid	Modified pan opening	
Vision panel lid		

Consult factory for other model configurations, options and accessories.





Project Name:	
Model Specified:	
Location:	
Item No:	Quantity:
AIA #:	SIS #:

Standard Model Features

REFRIGERATION SYSTEM

Performance rated refrigeration system
Natural, environmentally safe, high efficiency R-290 refrigerant ¹
Unique air flow distribution allows pan product to maintain 33° - 41°F
Automatic, hot gas condensate evaporator
Non-corrosive, plasticized fin evaporator coil
Easily serviceable, back mounted compressor

CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation Smooth, polished chrome drawer handles Stainless steel roll out drawers Magnetic snap in Santoprene™ drawer gaskets 8" deep, full length nylon cutting board Insulated lid Completely enclosed, vented and removable case back 5" casters

MODEL FEATURES

(12) $1/6$ size recessed pans, 4" deep		
Electronic control, off-cycle defrost		
Removable interior tub below pans		

¹ R-290 refrigerant meets all federal and state regulatory requirements.

APPROVAL:

Model Specifications

DIMENSIONAL DATA 9.0 (253 cu l) Net Capacity (cubic feet) 12 1/6 Size Pans (4" deep) Width, Overall (inches) 32 (813 mm) Depth, Overall (inches) 35 (890 mm) (including bumpers) Depth, Cutting Board (inches) 8 (203 mm) Height, Overall (inches) 42 1/4 (1073 mm) (including 5" casters) 2 Number of Drawers (two tier)

REFRIGERANT DATA

Condensing Unit Size (H.P.)	1/5	
Capacity (BTU per hour)*	1625	

ELECTRICAL DATA

Voltage (International)	115/60/1 (220/50/1)
Total Amps (International)	2.46 (1.85)
10 ft. Cord/Plug [attached] (International)	Yes (No)

SHIPPING DATA

Weight (pounds)	300 (137 kg)
Height - Crated (inches)	43 1/4 (1099 mm)
Width - Crated (inches)	40 (1016 mm)
Depth - Crated (inches)	37 1/4 (946 mm)

DRAWER PAN CONFIGURATIONS

Two Tier: (1) $12 \times 20 \times 6$ pan per drawer or (1) 1/2 size $\times 6 \& (2) 1/3 \times 6$ pans per drawer

* Rating @ +25°F evaporator, 90°F ambient
Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Model Plan Views





